

Cilindri molla ad azoto Serie M
Nitrogen gas spring M Series



M 50 TEM threaded

Table with 2 columns: *F1i = Forza finale isoteramica con 100% Cu, Isothermal end force at 100% Cu; **F1p = Forza finale politropica con 100% Cu, Polytrophic end force at 100% Cu

Table with 5 columns: Colore forza / Force color code, P (bar, psi), F0 (daN, lb), and values for GR, BU, RD, YW, BK


Importante: per la versione BK, indicare la pressione richiesta al momento dell'ordine. Questo garantisce che il cilindro venga consegnato pronto per l'utilizzo.
Important: For the BK version, please indicate the required pressure when placing the order. This ensures your cylinder is delivered ready for use.
P = pressione di carico nominale. P = nominal charging pressure

Technical drawing of the cylinder with dimensions and a photo of the Micro 32° connector with hoses.

Table with 8 columns: N2, temperature range, pressure change, max/min pressure, stroke, speed, max velocity, and maintenance kit

Large table with 10 columns: Codice Code, Cu, L, L min, *F1i, **F1p, VO, and PED, listing various cylinder models and their specifications.

Esempio di ordinazione/Order example = M 50-007-BU-TEM (codice/code + colore forza/force color code)



Fissaggi Flange mounts

39DM16X2A

